



HDW-300 T5

Powered by:

DOOSAN P126TI-II

300 kVA - 50 Hz

Generating Set Performance		50 Hz	
SERVICE		Continuous Service	Intermittent Service
Rated output	kVA	300	330
Active power output *	kW	240	264
Rated speed	r.p.m.	1.500	
Standard Voltage	V	400	
Voltage available	V	400/230 - 230/132 - 230	

Performance data refers to Standard Reference Conditions of ISO 8528 : + 25 °C , 100 m ALT, relative humidity 30 %

During running-in period the output increases by approx. 5 % which is taken into consideration at delivery.

Power reduction acc. to DIN ISO 3046. Standard values: Above 100 m ALT approx. 1 % per 100 m. Above 25 °C (77 °F) approx. 4 % per 10 °C (50 °F).

* Considering cos phi= 0,8

Prime Mover Performance		1.500 r.p.m.	
SERVICE		Continuous Service	Intermittent Service
Rated output	kW	265	294
Manufacturer		DOOSAN	
Engine model		P126TI-II	
4 stroke Diesel Engine - Injection type		DIRECT	
Aspiration type		TURBO CHARGED & INTERCOOLED	
Cylinders, number and arrangement		6 -L	
Bore x stroke	mm	123 x 155	
Total displacement	L	11,05	
Cooling system		WATER	
Lube oil specifications		SAE 15W 40 - API CD/CE	
Compression ratio		17 : 1	
Specific fuel consumption	L/h	63,1 - 47 - 31,3 - 16,9	
Specific oil consumption (at full load)	%	--	
Lube oil maximum capacity	L	23	
Lube oil minimum capacity	L	20	
Speed governor	Type	ELECTRONIC	
Steady state frequency at constant load	Type	<1,5*	
Governor class according to ISO 8528		G2	
Air filter		DRY	

(ICFN) : ISO-STANDARD POWER (10% overload permissible) and ISO-STANDARD FUEL STOP POWER (no overload permissible) according to DIN ISO 3046.

For constant speed and constant load.

(IFN) : ISO BRAKE FUEL STOP NET POWER for intermittent load acc. to DIN ISO 3046.

Performance data refers to Standard Reference Conditions of DIN ISO 3046: + 25 °C , 100 m ALT, relative humidity 30 % During running-in period the output increases by approx. 5 % which is taken into consideration at delivery. Power reduction acc. to DIN ISO 3046. Standard values: Above 100 m ALT approx. 1 % per 100 m. Above 25 °C (77 °F) approx. 4 % per 10 °C (50 °F).

Synchronous Generator *		
Pôles	N°	4
Winding connections (standard)		Star - serie
Frame mounting		SAE1 / 14"
Insulation	class	H
Enclosure (according to IEC-34-5)		IP 23
Exciter system		3 + N
Voltage regulator		A.V.R. (electronic)
Steady voltage precision		within ± 1,5% from no load to full loading with cosφ=0,8+1
Maintained short circuit current		3 In

*Alternator used by HIMOINSA Gensets meet the requirements of following Standard: IEC 34-1; CEI 2-3; ; VDE 0530; BS 4999-5000:NF 51-100,11

Generating Set Installation Data		1.500 r.p.m.
EXHAUST SYSTEM		
Max. exhaust temperature at full load	° C	590
	° F	1.094
Exhaust outlet diameter (Open skid - Soundproofed)	mm	95 - 140
Exhaust gas flow	m ³ /m	64,2
Heat rejected to coolant	kcal/kWh	--
Max. permissible restrictions	mmH ² O	600
AIR REQUIREMENT		
Cooling air flow	m ³ /s	--
Cooling air flow alternator	m ³ /m	--
Total cooling air flow (engine, alternator, combustion)	m ³ /m	--
ELECTRIC STARTING SYSTEM		
Starting motor output	kW	6,00
	CV	8,16
Minimum recommended battery capacity	Ah	150
Auxiliary voltage	Vcc.	24
LIQUID CAPACITY		
Lube oil system including sump, filters, etc.	L	24
Cooling system capacity	L	--
Antifreeze recommended percentage	%	--
FUEL TANK		
Fuel tank capacity Open Skid Genset	L	445
Autonomy (100%-75%-50%-25%)	h	7,05 - 9,47 - 14,22 - 26,33
Fuel tank capacity Soundproofed	L	445
Autonomy (100%-75%-50%-25%)	h	7,05 - 9,47 - 14,22 - 26,33

Generating Set transport data		
WEIGHT AND DIMENSIONS OPEN SKID GENSET		
Length	m - ft	3,50 - 11,48 (a)
Width	m - ft	1,16 - 3,8
Height	m - ft	1,75 - 5,74
Shipping volume seaworthy (Standard supplier)	m ³ - ft ³	7,10 - 250,40
Dry weight (with standard accessories)	kg - lb	2.650 - 5.830
WEIGHT AND DIMENSIONS SOUNDPROOFED GENSET		
Length	m - ft	3,80 - 12,46
Width	m - ft	1,40 - 4,59
Height	m - ft	2,30 - 7,54
Shipping volume seaworthy (Standard supplier)	m ³ - ft ³	12,23 - 431,22
Dry weight (with standard accessories)	kg - lb	4.200 - 9.240

(a) Chassis type K7. The leght datum refers to model with an external control panel (optional). Please consult for other configurations.

Local distributor



Factory: Ctra. Murcia - San Javier, Km. 23,6 30730
 SAN JAVIER (Murcia) España
 Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Export Fax +34968 19 04 20
 info@himoinsa.com www.himoinsa.com