



SW

SCANIA

HSW-255 T5

Powered by:

SCANIA DC9 65A (10-93)

250 kVA at 50 Hz

Directive 97/68/EC (Stage II)



Generating Set Performance		50 Hz	
SERVICE		Continuous Service	Intermittent Service
Rated output	kVA	250	275
Active power output *	kW	200	220
Rated speed	r.p.m.	1.500	
Standard Voltage	V	400	
Voltage available	V	400 / 230 - 230 / 132 - 230	

Performance data refers to Standard Reference Conditions of ISO 8528 : + 25 °C , 100 m ALT, relative humidity 30 %

During running-in period the output increases by approx. 5 % which is taken into consideration at delivery.

Power reduction acc. to DIN ISO 3046. Standard values: Above 100 m ALT approx. 1 % per 100 m. Above 25 °C (77 °F) approx. 4 % per 10 °C (50 °F).

* Considering cos phi= 0,8

Prime Mover Performance		1.500 r.p.m.	
SERVICE		Continuous Service	Intermittent Service
Rated output	kW	225	247
Manufacturer		Scania	
Engine model		DC9 65A (10-93)	
4 stroke Diesel Engine - Injection type		DIRECT	
Aspiration type		TURBOCHARGED and after cooled	
Cylinders, number and arrangement		5 - L	
Bore x stroke	mm	127 x 140	
Total displacement	L	8,87	
Cooling system		WATER	
Lube oil specifications		ACEA E3-96 • CCMC D5 API CF	
Compression ratio		18 : 1	
Specific fuel consumption	L / h	51,54	56,87
Specific oil consumption (at full load)	%	0,15	
Lube oil maximum capacity	L	29	
Lube oil minimum capacity	L	23	
Speed governor	Type	Electronic	
Air filter	Type	DRY light duty	

PRIME POWER (P.R.P.): The prime power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

STAND BY POWER: Is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overload is permissible for this use.

Synchronous Generator *		
Pôles	N°	4
Winding connections (standard)		Star - serie
Frame mounting		SAE 1 -14"
Insulation	class	H
Enclosure (according to IEC-34-5)		IP 23
Exciter system		3+N
Voltage regulator		A.V.R. (electronic)
Steady voltage precision		within ± 1,5% from no load to full loading with cosφ=0,8±1

*Alternator used by HIMOINSA Gensets meet the requirements of following Standard: IEC 34-1; CEI 2-3; VDE 0530; BS 4999-5000:NF 51-100,11



Generating Set Installation Data		
EXHAUST SYSTEM		
Max. exhaust temperature at full load	° C	442
	° F	827,6
Exhaust gas flow	kg / h	1.260
Heat rejected to exhaust	kcal/kWh	529,5
Maximum allowed back pressure	mm/H2O	1.000
AIR REQUIREMENT		
Air requirement for combustion at 100% load / rated speed	m3/h	1.076
ELECTRIC STARTING SYSTEM		
Starting motor output	kW	5,5
	CV	7,48
Minimum recommended battery capacity	Ah	--
Auxiliary voltage	Vcc.	24V
LIQUID CAPACITY		
Lube oil system including sump, filters, etc.	L	30
FUEL TANK CAPACITY		
Open Skid Genset	L	445
Soundproofed	L	445

Generating Set transport data		
WEIGHT AND DIMENSIONS OPEN SKID GENSET		
Length	m - ft	3,50 - 11,48 (a)
Width	m - ft	1,16 - 3,80
Height	m - ft	1,85 - 6,08
Shipping volume seaworthy (Standard supplier)	m³ - ft³	7,53 - 265,23
Dry weight (with standard accessories)	kg - lb	2.080 - 4.576*

WEIGHT AND DIMENSIONS SOUNDPROOFED GENSET		
Length	m - ft	3,80 - 12,46
Width	m - ft	1,40 - 4,59
Height	m - ft	2,10 - 6,90
Shipping volume seaworthy (Standard supplier)	m³ - ft³	11,19 - 394,62
Dry weight (with standard accessories)	kg - lb	3.320 - 7.304*

(a) Chassis type K7. The leght datum refers to model with an external control panel (optional). Please consult for other configurations.



HIMOINSA company with quality certification ISO 9001
HIMOINSA gensets are compliant with EC mark which includes the following directives:

- ISO 13857:2008 Machinery safety.
- 2006/95/EC Low voltage.
- 89/336/EEC Electromagnetic compatibility.
- 200/14/EC Sound Powr leve. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2002/88/EC & 2004/26/EC)

Local distributor



Factory: Ctra. Murcia - San Javier, Km. 23,6 30730
SAN JAVIER (Murcia) España
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Export Fax +34968 19 04 20
info@himoinsa.com www.himoinsa.com